



JOHN DEERE


ENGINE PERFORMANCE CURVE

Rating: 60 Hz - 558hp (416kW) @ 1800 RPM
 Application: Marine

PowerTech™ 13.5L Engine

Model: 6135SFM85

Generator Efficiency (%)	Power Factor	Calculated Gen-Set Rating		Prime Power	10% Overload Power
		kWe	kVA	hp (kW)	hp (kW)
88-92	0.8	366-383	457-479	558 (416)	614 (458)



REFERENCE CONDITIONS

Air Intake Restriction.....12 in.H₂O (3 kPa)
 Exhaust Back Pressure..... 30 in.H₂O (7.5 kPa)

Rated speed and power
 Gross power guaranteed within ±5% at ISO 8665/SAE J1228 and ISO 3046/SAE J1995
 Test conditions:

77 °F (25 °C) air inlet temperature
 29.31 in.Hg (99 kPa) barometric pressure
 104 °F (40 °C) fuel inlet temperature
 0.853 fuel specific gravity @ 60 °F (15.5 °C)

Ambient air temperature is defined to be the temperature of ambient air close to operating vessel that is not influenced in any manner by operating characteristics of the vessel (free field temp).

Conversion factors: Power: kW = hp x 0.746
 Fuel: 1 gal = 7.1 lb, 1 L = 0.85 kg
 Torque: N·m = lb·ft x 1.356

All values from currently available data. Subject to manufacturing and measurement variations and to change without notice.
 Actual performance is subject to application and operation conditions outside of John Deere control.

All pressures shown in gauge pressure

Notes:
Marine Generator: The Marine generator engine rating is the power available under normal varying electrical load factors for an unlimited number of hours per year in commercial applications. This rating incorporates a 10% overload capability, and conforms to ISO 8528 prime power. Average load over a 24-hour period shall not exceed 67% of the prime rating, of which no more than 2 hours are between 100% and 110% of the prime rating.

Constant speed engines are not certified for constant speed propulsion applications (i.e. variable pitch propeller, hybrid propulsion system).

Possible applications: This rating is used for applications that require constant speed operation in power generation or auxiliary applications such as generators and hydraulic pumps.

Designed/Calibrated to meet:	Certified by:
<ul style="list-style-type: none"> EPA Marine Tier 3 Constant Speed Auxiliary (40 CFR 1042) IMO Tier II Compliant (MARPOL Annex VI) 	
Ref: Engine Emission Label	30-Oct-18

Performance Curve: 6135SFM85_F

All values at rated speed, power, and standard conditions, per SAE J1995 unless otherwise noted.

Engine Installation Criteria

General Data

Model	6135SFM85		
Number of Cylinders	6		
Bore	132 mm	5.20	in
Stroke	165 mm	6.50	in
Displacement	13.5 L	824	in ³
Compression Ratio	16.0:1		
Valves per Cylinder, Intake/Exhaust	2/2		
Combustion System	Direct injection		
Firing Order	1-5-3-6-2-4		
Engine Type	In line, 4 Cycle		
Aspiration	Turbocharged and Aftercooled		
Aftercooling System	Seawater cooled		
Engine Crankcase Vent System	Closed		

Cooling System*

Jacket Water Heat Rejection**	275.8 kW	15698	BTU/min
Aftercooler Heat Rejection	132 kW	7513	BTU/min
Coolant Flow	238 L/min	63	gal/min
Min. Coolant Pump Inlet Pressure	30.3 kPa	4.4	psi
Thermostat Start to Open	82 °C	180	°F
Thermostat Fully Open	92 °C	197	°F
Engine Coolant Capacity, HE	38 L	10	gal
Min. Coolant Fill Rate	12 L/min	3.2	gal/min
Min. Pressure Cap	110.3 kPa	16	psi
Max. External Coolant Restriction	40 kPa	5.8	psi
Normal Operation Max Top Tank Temperature	100 °C	212	°F
≤ 5% of Total Operating Time Top Tank Temperature	100-105 °C	212-230	°F
Absolute Max Top Tank Temperature	105 °C	221	°F
Return Fuel Heat Rejection	1 kW	64.265	BTU/min
Engine Radiated Heat	52 kW	2976	BTU/min

* The cooling system should be capable of typical at ambient up to the maximum conditions in which the vessel will operate.

Typical operation is defined as the average load sustainable in the vessel over 10 min.

** Reference 32 °C Sea Water Temperature

Physical Data

Length to rear face of block	1335 mm	52.6	in
Length to rear face of flywheel housing (SAE #1)	1444 mm	56.8	in
Length maximum	1818 mm	71.6	in
Width maximum	1063 mm	41.9	in
Height, crank centerline to top	812 mm	32	in
Height, crank centerline to bottom	364 mm	14.3	in
Weight, with oil, no coolant (includes engine, flywheel housing, flywheel, and electronics)	1426 kg	3143	lb
Center of Gravity Location, X-axis From Rear Face of Block	476 mm	18.7	in
Center of Gravity Location, Y-axis Right of Crankshaft	-9 mm	-0.4	in
Center of Gravity Location, Z-axis Above Crankshaft	250 mm	9.84	in
Max. Allowable Static Bending Moment At Rear Face of Flywheel Housing (for installations up to 5-G)	814 Nm	600	lb-ft
Thrust Bearing Load Limit, Forward Continuous	5.4 kN	1214	lbf
Thrust Bearing Load Limit, Forward Intermittent	8.1 kN	1821	lbf
Thrust Bearing Load Limit, Rearward Continuous	2.5 kN	562	lbf
Thrust Bearing Load Limit, Rearward Intermittent	4 kN	899	lbf

Electrical System

Min. Recommended Battery Capacity, 12V @32 °F (0 °C)	1900	amps
Min. Recommended Battery Capacity, 24V @32 °F (0 °C)	925	amps
Starter Rolling Current, 12V @32 °F (0 °C)	920	amps
Starter Rolling Current, 24V @32 °F (0 °C)	600	amps
Min. Voltage at ECU during Cranking, 12V	6	volts
Min. Voltage at ECU during Cranking, 24V	10	volts
Max. Allowable Start Circuit Resistance, 12V	0.002	ohms
Max. Allowable Start Circuit Resistance, 24V	0.0012	ohms
Electrical Component Maximum Temperature Limit	125 °C	257 °F
Maximum ECU Temperature	105 °C	221 °F

Performance Curve: 6135SFM85_F

All values at rated speed and power at standard conditions per SAE J1995 unless otherwise noted.

Engine Installation Criteria

Fuel System

ECU Description	L15		
Fuel Injection Pump	EUI		
Governor Type	Electronic		
Volumetric Fuel Consumption, Prime	104 L/hr	27.5 gal/hr	
Mass Fuel Consumption, Prime	88.5 kg/hr	195 lb/hr	
Total Fuel Volumetric Flow	159 L/hr	42.0 gal/hr	
Total Fuel Mass Flow	135 kg/hr	298 lb/hr	
Max. Fuel Inlet Restriction*	30 kPa	120 in.H2O	
Max. Fuel Inlet Pressure	24 kPa	96 in.H2O	
Max Fuel Return Pressure	35 kPa	141 in.H2O	
Normal Operation Fuel Temperature	40 °C	104 °F	
Max. Fuel Inlet Temperature	100 °C	212 °F	
Min. Recommended Fuel Line Inside Diameter	6.79 mm	0.27 in	
Min. Recommended Fuel Line Size	5 (-) AN		
Primary Fuel Filter	10 mic		
Secondary Fuel Filter	2 mic		

Lubrication System

Oil Pressure at 1800 RPM**	280 kPa	41 psi	
Max. Crankcase Pressure	2 kPa	8 in.H2O	
Maximum Installed Angle, Front Down	0 deg		
Maximum Installed Angle, Front Up	12 deg		
Engine Angularity Limits Any Direction, Continuous***	20 deg		
Engine Angularity Limits Any Direction, Intermittent***	30 deg		

Seawater Pump System

Seawater Pump Flow	389 L/min	103 gal/min	
Max. Suction Lift	3 m	9.8 ft	
Max. Outlet Pressure	140 kPa	20 psi	
Max. Inlet Restriction	30 kPa	4 psi	

* With clean filters

** With John Deere Plus-50 II™ 15w-40, not applicable with break in oil.

*** With 1904 option

Air Intake System

Engine Air Flow	38.0 m ³ /min	1342 ft ³ /min	
Intake Manifold Pressure	261 kPa	37.9 psi	
Manifold Air Temperature	58 °C	136 °F	
Maximum Manifold Air Temperature	87 °C	189 °F	
Max. Allowable Temperature Rise, Ambient Air to Engine Inlet	17 °C	30 °F	
Max. Air Intake Restriction, Clean Air Cleaner	3 kPa	12 in.H2O	
Max. Air Intake Restriction, Dirty Air Cleaner	6.25 kPa	25 in.H2O	
Min. Ventilation Area	0.234 m ²	362 in ²	

Performance Data

Prime Power	416 kW	558 hp	
10% Overload Power	458 kW	614 hp	
Rated Speed	1800 RPM		
Low Idle Speed	1000 RPM		
Prime Torque	2209 Nm	1629 lb-ft	
BMEP, Prime	2056 kPa	298 psi	
Rated Pferdestärke, Prime (metric hp)	566 ps		
Front Drive Capacity, Intermittent	542 Nm	400 lb-ft	
Front Drive Capacity, Continuous	542 Nm	400 lb-ft	
Software and Label Convertible to 50 Hz?	YES		
Friction Power @ Rated Speed	41.5 kW	55.6 hp	

Exhaust System

Exhaust Flow	83 m ³ /min	2931 ft ³ /min	
Exhaust Flow @ gas STP	36.1 m ³ /min	1275 ft ³ /min	
Exhaust Temperature	411 °C	771.8 °F	
Max. Allowable Exhaust Restriction	7.5 kPa	30 in.H2O	
Max. Shear on Turbocharger Exhaust Outlet	11 kg	24.3 lb	
Max. Bending Moment on Turbocharger Exhaust Outlet	7 Nm	15.4 lb-ft	
Min. Exhaust Pipe Diameter, Dry	139.7 mm	5.5 in	
Min. Exhaust Pipe Diameter, Wet	152.4 mm	6.0 in	

Performance Curve: 6135SFM85_F

All values at rated speed and power at standard conditions per SAE J1995 unless otherwise noted.

Engine Installation Criteria

Engine Performance Data Table

Engine Power	Crank Power		Crank Torque		Fuel Consumption		BSFC
	kW	hp	Nm	lb-ft	L/hr	gal/hr	
25%	104	140	552	407	29.0	7.7	237
50%	208	279	1104	814	53.4	14.1	218
75%	312	419	1656	1221	78.6	20.8	214
100%	416	558	2208	1629	104.2	27.5	213
110%	458	614	2429	1792	116.2	30.7	216

Performance Curve: 6135SFM85_F

All values at rated speed and power at standard conditions per SAE J1995 unless otherwise noted.